

Characterization of High Curie Temperature Piezocrystals: doped $\text{Pb}(\text{Yb}_{1/2}\text{Nb}_{1/2})\text{O}_3$ - PbTiO_3 and BiScO_3 - PbTiO_3

Shujun Zhang, Clive A. Randall and Thomas R. Shrout



Material Research Institute, Pennsylvania State University
University Park, PA, 16802

Acknowledgment:

This work is supported by ONR, DARPA and NIH.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 00 JUN 2003		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE Characterization of High Curie Temperature Piezocrystals: doped Pb(Yb1/2Nb1/2)O3-PbTiO3 and BiScO3-PbTiO3				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Material Research Institute, Pennsylvania State University University Park, PA, 16802				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES See also ADM001697, ARO-44924.1-EG-CF, International Conference on Intelligent Materials (5th)(Smart Systems & Nanotechnology)., The original document contains color images.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 7	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			



Phase diagram of (1-x)PYN-xPT and (1-x)BS-xPT systems



(After Rich Eitel reference)



The phase diagram show that the MPBs for PYN-xPT systems are located at $x=0.5$ and $x=0.64$ for BS-xPT system. The Curie temperatures are around 350 °C and 460 °C, respectively.

Characterization of zinc doped PYN-PT single crystals





Along $\langle 001 \rangle$ orientation, the Curie temperature is around 325 $^{\circ}\text{C}$ and phase transition temperature around 212 $^{\circ}\text{C}$, the strain is low-hysteresis when the field at 20kV/cm, the piezoelectric coefficient is around 1700pC/N

Characterization of tetragonal BSPT single crystals





The Curie temperature was found to be ~460°C, after high temperature poling, the piezoelectric coefficient is around 250pC/N, coupling factor is 74% at room temperature.

Characterization of rhombohedral BSPT crystals



The BSPT crystal along $\langle 001 \rangle$ direction, the Curie temperature around 427°C , the piezoelectric coefficient 850pC/N and coercive field 20kV/cm .

Rhombohedral BSPT crystal along $\langle 110 \rangle$ direction



Along $\langle 110 \rangle$ direction, the Curie temperature is around 440°C while the phase transition temperature at 330°C . The coercive field is 24kV/cm and piezoelectric coefficient about 400pC/N .

Conclusion and Future Works

- High Curie temperature single crystal PYNT and BSPT have been grown using flux method
 - Large Coercive field – domain stability ($E_c \sim 10\text{-}30\text{ kV/cm}$)
 - Promising piezoelectric and electromechanical properties in rhombohedral phase which expand the application temperature range to about 300°C ($d_{33} \sim 800\text{-}2000\text{ pC/N}$)
 - Tetragonal BSPT crystal has very low dielectric constant at room temperature which is candidate for the single-element transducer ($K \sim 300$)
- * Try to find new method to grow large rhombohedral phase BSPT and PYNT crystals, explore excellent properties of the new materials.